

TRV-3500

Customized, Trailer-Mounted
Hot Water Pressure Washer System

- Single Axle
- Customized Hot-Water Pressure Washer
- 3,000 lb Load Capacity
- 200 Gallon Water Tank
- Swing-Away Tongue

■ 200-gallon white **High-Density Polyethylene Water Tank** comes standard with the trailer and features a 7-inch access port plus a 2-inch drain plug, ¾-inch float valve, and a 50-mesh outlet filter.

▼ **Optional Hose Reels** hold up to 150 ft. of high-pressure hose and quick connects to chassis.

■ Made of extra-durable 2-by-4 inch, 10-gauge formed channel, and covered with a powder-coated epoxy black finish for weather protection; this **Heavy-Duty Chassis** features recessed lights with all electrical wiring recessed within the frame.

■ The single-axle trailer comes with standard **Electric Brakes with Break Away Kit** or optional hydraulic brakes.

▼ Made to handle up to 1,000 lbs, the swivel jack **Trailer Tongue Assembly**, with a 2-inch ball coupler for quick and easy hookup of the trailer. Two ½-inch chains are also included for additional safety.

► **Innovative Dual Drain System.** Primary drain for easy daily use purposes. Secondary drain allows tank to be emptied when winterizing the unit.



▲ 3-way ball valve makes it easy to **Switch Water Sources** from the holding tank to direct water feed from a hose faucet.

► Made of durable 14 gauge steel, **Optional Rear-Mount Utility Rack and Side Saddle Boxes** provide generous tool storage.



▲ Wheel and axle assembly features an **Industrial Undercarriage** leaf-spring suspension of up to 3,000 lbs. with 15-inch, white rimmed wheels and sturdy fenders.

TRV-3500 Trailer
Shown with pressure washer and options



► **Durable Swing-Away Tongue** (rated for 3,500 lbs) allows trailer to be stored in smaller area.

WHY CHOOSE THE TRV TRAILER?

Landa Kärcher Group has made customizing a trailer-mounted wash system for on-site cleaning an easy two-step process.

Step 1: Select from five series of portable, self-contained, industrial-grade, hot-water pressure washers.

Step 2: Add any options and accessories, such as hose reels, rear utility rack, side saddle tool boxes, etc. to enhance the performance.

The TRV-3500 trailer is made of extra-rugged 2-by-4 inch, 10-gauge formed channel. The wheel and axle assembly feature leaf-spring suspension of up to 3,500 lbs. and 15-inch, white rimmed wheels. A powder-coated epoxy finish gives the entire package added weather protection.



TRV Hot-Water Pressure Washer Selection



PDHW	PGHW	PGDC	MHP	MHC**
4 Models Available	5 Models Available	3 Models Available	3 Models Available	6 Models Available
4.7 GPM	3.5-5.0 GPM	3.8-4.7 GPM	3.5-3.8 GPM	2.5-3.5 GPM
3500 PSI	3000-5000 PSI	3500 PSI	3000-3500 PSI	2500-3500 PSI
Diesel	Gasoline	Gasoline	Gasoline	Gasoline
Belt Drive Pump	Belt Drive Pump	Belt Drive Pump	Belt Drive Pump	Direct Drive Pump
948-998 lbs	725-1285 lbs	630-697 lbs	555-595 lbs	550-600 lbs

**Comes standard with 12V feed pump



Model #	Part #	Axle	GVWR (lbs)	Water Tank	Ship Wt (lbs)
TRV-3500	1.103-820.0	Single	3000	200 gal	1072

Distributed by:

Field Installed Options & Accessories

8.917-554.0	High Pressure Hose Reel ♦ (100' capacity, hose not included)	8.917-399.0	PGDC Mounting Assembly ♦
8.917-555.0	Low Pressure Hose Reel ♦ (100' capacity, hose not included)	8.917-398.0	Hydraulic Brakes ♦
8.917-583.0	Wheel Kit (2 chrome wheels)	8.924-493.0	2-5/16" Ball Hitch Coupler ♦
8.920-434.0	PDHW Mounting Assembly ♦	8.917-560.0	Utility Rack (rated for up to 150 lbs)
8.917-299.0	PGHW Mounting Assembly ♦*	8.917-558.0	Saddle Box (each)
8.915-494.0	MHC Mounting Assembly ♦	8.917-556.0	Saddle Boxes (2 boxes) ♦
8.917-300.0	MHP Mounting Assembly ♦	8.917-557.0	Rock Guard ♦
		8.917-559.0	Rock Guard

♦ Factory Installed

* PGHW5-50524E Not Compatible